
BEKT-S501CAⅡ




Barudan
THE MOST ADVANCED EMBROIDERY MACHINE SINCE 1959

Accessories




Wide Cap Frame



Sock Frames




Frames for Finished Products



Detachable Table



Steel Stand



Bobbin Winder (BN-Ⅳ)


B-NET (Option)

Complete Production Management Software

B-NET is an embroidery machine networking system for seamless transfer of designs and offers the following.

Explorer → Editing → Distribution → Status and Stats → Reporting → Maintenance

Design File Server
Design transfer via LAN connection




Sewing Machine Manager
Machine status on floorplan



Design File Explorer
Design file viewing and managing



Design File Function Editor
Design editing and function changes



B-NET - Reporting
Productivity & status reporting

B-NET WEB
Machine status, history, and maintenance activities on browser (tablet compatible)

B-NET WEB API ※Optional
Web API lets B-NET integrate with the user's current order entry software



BARUDAN CO., LTD.

■Sales Headquarter
1-1 Dainichi, Minamiobuchi, Ichinomiya-city, Aichi-pref., 491-0014 Japan
Phone +81 586-76-1137
Fax +81-586-77-1499
URL https://www.barudan.co.jp/
E-mail info@barudan.co.jp

Agent:

We reserve the right to change specifications without notice for the purpose of product improvement.

2025-10


BEKT-S501CAII


More Productivity with Reduced Changeover Time by Air Clamp Frame

MODEL
BEKT-S501CAII



Features


Cross Hair Laser Marker



Air Clamp Base Frame



Foot Pedal



Clamp Frame (Mid. Size)

Air Clamp Frames [option]


Clamp Frame (S. Size)


Clamp Frame (L. Size)


Clamp Frame for Belts

A Variety of Air Clamp Frames (mm)
S : 50×80　100×80
L : 120×250
(Designated Table Required)
for Belts : 35 ~ 65×250
(Designated Table Required)
Line-up

Name Drop

Separates names in multiple name design for view and sewing purposes.




Name Drop Drive Mode



Name List Display



Thumbnail Display





New Tensioner

New thread tensioning system ensures better tensioning and improved thread break accuracy



- Frame Centering Function
- Frame Limit Function — Able to restrict machine operation when a design does not fit to the frame or when there is a risk of a needle bar hitting the frame.
- Shortcuts — Customize most-used icons to save time.
- LAN Connector Standard, 1 USB port
- Touch screen (8.4 inch, Resolution 800×600)
- 70 million stitch capacity, 100 memory locations





■Machine Specifications／Main Dimensions

MODEL	Embroidery Area (mm)	Cap Frame (mm)	Clamp Frame (mm)	Number of Needles	Stitch Length (mm)	Speed (rpm)	Power Supply (v)	Power Consumption (kw)	Dimensions (mm)							Weight (kg)
									L	W	H	A	B	C	E	
BEKT-S501CAII	250×400	72×360	① 70×120 ② 90×140 ③140×120	5	0.1～12.7	(Tubular Frame) 200～1200 (Clamp Frame) (Cap Frame) 200～1000	1φ100～240	0.225	600	930	965	680	690	765	810	71

■ The embroidery area indicated above allows for maximum pantograph movement. The frame used may restrict the actual embroidery field size.
■ A separate air compressor with recommendable 1 kW is required for Air Clamp Frame.
■ Machines and Specifications are subject to change at any time without prior notice.

Barudan
THE MOST ADVANCED EMBROIDERY MACHINE SINCE 1959